
Lockup Flagpole secure and effective



Lockup Flagpole

secure and effective



Lockup Flagpole

Well-established, lockable flagpole for banners and flags. Thanks to the internal hoisting mechanism, this flagpole is particularly suitable for public places such as pedestrian zones, outside public buildings or shopping streets.

The Lockup Flagpole is available in sizes from 5 m to 12 m and is equipped with an external plastic lock. After opening, the flag can be manually hoisted with the internal halyard.



Lockup Flagpole

The plastic head on the flagpole guides the rope from inside the pole to the outside. The special cord is designed for very heavy loads and has a breaking load of 600 kg. The flag is fixed to a galvanized ring at the end of the halyard and lengthwise down the flagpole with the supplied plastic tubes. A counterweight enables the smooth lowering of the flag. The flagpole is fixed in place with a ground socket and the appropriate center ring.

Technical Data: Lockup Flagpole

Height	Version	Diameter	Weight	Pack Length
5 m	1-piece	80 mm	10,0 kg	5,5 m
6 m	1-piece	80 mm	12,0 kg	6,5 m
7 m	1-piece	80 mm	13,6 kg	7,5 m
8 m	2-piece	100/80 mm	19,5 kg	4,5 m
9 m	2-piece	101/80 mm	22,0 kg	6,0 m
10 m	2-piece	101/80 mm	24,2 kg	6,0 m
11 m	2-piece	101/80 mm	25,9 kg	6,0 m
12 m	2-piece	101/80 mm	28,0 kg	6,5 m

Flagpoles are aluminum, available in colorless anodized (silver grey) or powder-coated white (RAL 9010) versions. More colors on request.

Maintenance:

The plastic tubes must be checked from time to time and missing tubes or torn loops on the flag must be replaced immediately. It is important to replace all worn parts immediately.

Remarks:

Always attach the weight, with or without a flag. The flag must have a loop for the plastic tubes every 60 cm. Always fix the weight to the lowest flag loop and to the lowest plastic tube! In stormy weather (Beaufort 8+ winds) the flag must be taken down for safety reasons.